

# PE CLEANER SPECIAL

## CLEANER FOR PE, PP, PVDF AND PB



### STORAGE CONDITIONS

At least 24 months in the unopened package and stored between +5°C and +25°C. Close the container properly and store in a dry, cool and frost-free location. Limited shelf life after opening.

### PRODUCT DESCRIPTION

Cleaner for PE, PP, PVDF and PB.

### FIELD OF APPLICATION

For pipes and fittings of PE, PP, PVDF and PB to be welded. Also suitable for cleaning welding equipment. Use in combination with the Griffon Cleaner Cloth.

### PROPERTIES

- Powerful cleaning properties
- Rapid and complete vaporization
- With special dosing cap

### APPLICATION

**Coverage:** Indication of the number of joints per 1 L:

Ø	32	40	50	63	75	90	110	125	160	200	250
#	800	700	650	550	330	250	160	140	90	50	35

### Directions for use:

1. Apply on a clean Griffon Cleaner Cloth. 2. Clean the surfaces. 3. Remove any condensation with a clean Cleaner Cloth and allow to dry. Properly close the container immediately after use.

### TECHNICAL SPECIFICATIONS

**Chemical base:** Ethanol (very high purity)

**Colour:** Colourless

**Viscosity:** approx. 1 mPa.s.

**Density:** approx. 0.8 g/cm<sup>3</sup>

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.