

UNIT ALARM 1 | 2 | GSM

Beacon/flashing alarm with buffer battery

UNIT ALARM 1: beacon 90 dbA

UNIT ALARM 2: beacon 90 dbA and lashing alarm UNIT

ALARM GSM: beacon 90 dbA, lashing alarm and kit GSM



GENERAL FEATURES

- Power supply 1 ~ 50/60Hz 230V ±10%;
- 1 Normally open contact for alarm signal from volt free contact ;
- 1 Normally close contact for alarm signal from volt free contact ;
- Green led indicating mains supply;
- Red led indicating alarm;
- Red led indicating beacon disabled;
- Alarm beacon 90dB 12Vcc;
- Red flashing led 12Vcc (mod. UNIT ALARM 2 and UNIT ALARM GSM);
- GSM modem with antenna and transmitter settable for signalling alarm activation to mobile phones.
GSM phone-card not included (mod. UNIT ALARM GSM);
- Pushbutton for enabling the acoustic alarm;
- Pushbutton for disabling the acoustic alarm;
- Internal selector for selecting alarm restoration mode in automatic or manual;
- Internal selector for activation of the auto switch-off beacon timer ;
- Trimmer for auto switch-off time delay;
- Internal sealed battery 12Vcc 1,2Ah;
- Box in ABS, IP55;
- Ambient temperature: -5/+40 °C;
- Relative humidity 50% a 40 °C (not condensed).

TECHNICAL DATA

| UNIT ALARM 1 2 | COD. | Alimentazione | Lampeggiante | Press. sonora | Tensione | Autonomia | Dimensioni | | | | Peso |
|------------------|-------|---------------|--------------|----------------|----------|-----------|------------|-----|-----|----------|--------|
| | | Power supply | Buzzer | Sound pressure | Voltage | Endurance | Dimensions | | | | Weight |
| | | V~ | | dB | VDC | h | H | L | W | Material | Kg |
| UNIT ALARM 1 | 01500 | 1~230 V | - | 90 | 12 | 24 | 320 | 240 | 190 | ABS | 1,5 |
| UNIT ALARM 2 | 01501 | 1~230 V | ROSSO/RED | 90 | 12 | 24 | 320 | 240 | 190 | ABS | 1,5 |
| UNIT ALARM GSM | 01502 | 1~230 V | ROSSO/RED | 90 | 12 | 24 | 320 | 240 | 190 | ABS | 2,5 |

NOTE:

Please contact our technical/sales department for different implementations 01473 462046